



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/977,338	10/16/2001	Yoshiyuki Kamihara	110880	1638

25944 7590 11/28/2006

OLIFF & BERRIDGE, PLC
P.O. BOX 19928
ALEXANDRIA, VA 22320

EXAMINER

MALEK, LEILA

ART UNIT	PAPER NUMBER
----------	--------------

2611

DATE MAILED: 11/28/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 09/977,338	Applicant(s) KAMIHARA, YOSHIYUKI	
	Examiner Leila Malek	Art Unit 2611	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 16 October 2001.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-36 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-36 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 16 October 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>10/16/01-12/6/01-06/04/03-09/16/04</u>
<u>02/22/05</u> | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Priority

1. Acknowledgment is made of applicant's claims for foreign priorities under 35 U.S.C. 119(a)-(d). The certified copies have been filed in parent Application No. 09/977,338, filed on 10/16/2001.

Information Disclosure Statement

2. The information disclosure statements (IDS) submitted on 10/16/01, 12/06/01, 06/04/03, 09/16/04, and 02/22/05 have been considered and made of record by the examiner.

Claim Objections

3. Claim 1 is objected to because of the following informalities: as to claim 1, lines 5-6, "detecting between which two edges a data edge is located" needs to be replaced by "detecting between which two clock edges a data edge is located". Appropriate action is required.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 1, 2, 5, 8, and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota et al. (hereafter, referred as Hirota) (US 6,567,484), in view of Tanabe et al. (hereafter, referred as Tanabe) (US 4,672,639).

As to claim 1, Hirota discloses an apparatus comprising: an edge detection circuit (see Fig. 4, 23-2) detecting between which two clock edges a data edge is located (see Fig. 5 and column 3, lines 9-30), the two edges being among edges of first to N-th clocks having the same frequency but mutually different phases (see the abstract and column 2, lines 21-29); and a clock selection circuit which selects one clock (i.e. clock #7) from among the first to N-th clocks (see column 3, lines 28-30), based on detection information from the edge detection circuit. Hirota discloses all the subject matters claimed in claim 1, except that the selected clock has been used as a sampling clock. Tanabe, in the same field of endeavor, discloses a sampling pulse generator, which receives a plurality of clock signals having the same frequency and phase differences. Tanabe further discloses an additional signal (interpreted as data signal) is also inputted to the edge detector (see Fig. 1), wherein phase relationship data are constructed and assembled and an optimum one of the clock signals is selected and outputted based on the phase data as the recovered sampling clock (see the abstract and column 3, lines 30-45, and see column 1, lines 10-16). It would have been obvious to one of ordinary skill in the art at the time of invention to use the optimum clock selected from a plurality of clocks (i.e. the clock which samples the data in the middle) as the sampling clock, in order to sample the data correctly and therefore more accurately recognize the incoming data (see column 1, lines 62 to column 2, line 9).

As to claim 2, Tanabe further discloses that the edge detection circuit comprises: a first holding circuit (see Fig. 3, e.g. 310) which holds data (CRS

Art Unit: 2611

interpreted as data) by using the first clock (CK0), . . . a J-th holding circuit (see Fig. 3, e.g. 314), which holds data by using a J-th clock (CK4), . . . and an N-th holding circuit (see Fig. 3, e.g. 317) which holds data by using the N-th clock (CK7); and a first detection circuit (e.g. AN0) which detects whether or not there is a data edge between the edges of the first clock and a second clock, based on data held in the first holding circuit and a second holding circuit, . . . a J-th detection circuit (e.g. AN4) which detects whether or not there is a data edge between the edges of the J-th clock (CK4) and a (J+1)-th clock (CK5), based on data held in the J-th holding circuit (314) and a (J+1)-th holding circuit (315), . . . and an N-th detection circuit (AN7) which detects whether or not there is a data edge between the edges of the N-th clock (CK7) and the first clock (CK0), based on data held in the N-th (317) and first (310) holding circuits, and wherein the clock selection circuit 35 selects a clock from among the first to N-th clocks, based on edge detection information from the first to N-th detection circuits, and outputs the selected clock as the sampling clock. It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota as suggested by Tanabe to accurately determine the edge of the data (see column 4, lines 10-24) and find the optimum sampling clock.

As to claim 5, Hirota and Tanabe disclose all the subject matters claimed in claim 1, except that the number of clocks N of the first to N-th clocks is such that N=5. However, since applicant does not disclose any advantage for using 5 clocks in the system, therefore, it is a matter of design choice to sample the signal with 5 clocks and it would have been obvious to one of ordinary skill in the

Art Unit: 2611

art at the time of invention to use 5 clocks in the system to sample the signal to meet the system requirements.

As to claim 8, Hirota discloses that the clock selection circuit selects from the first to N-th clocks a clock having an edge that is shifted by a given set number M (e. g. 3 to obtain clock #7) of edges from a data edge (see Fig. 5).

As to claim 14, Hirota discloses an apparatus comprising: an edge detection circuit (see Fig. 4, 23-2) detecting between which two clock edges a data edge is located (see Fig. 5 and column 3, lines 9-30), the two edges being among edges of first to N-th clocks having the same frequency but mutually different phases (see the abstract and column 2, lines 21-29); and a clock selection circuit which selects one clock (i.e. clock #7) from among the first to N-th clocks (see column 3, lines 28-30), based on detection information from the edge detection circuit. Hirota discloses all the subject matters claimed in claim 14 except that the selected clock has been used as a sampling clock. Tanabe, in the same field of endeavor, discloses a sampling pulse generator, which receives a plurality of clock signals having the same frequency and phase differences. Tanabe further discloses an additional signal (interpreted as data signal) is also inputted to the edge detector (see Fig. 1), wherein phase relationship data are constructed and assembled and an optimum one of the clock signals is selected and outputted based on the phase data as the recovered sampling signal (see the abstract and column 3, lines 30-45, and see column 1, lines 10-16). Hirota further discloses that the clock selection circuit selects from the first to N-th clocks a clock having an edge that is shifted by a given set number M (e. g. 3 to

Art Unit: 2611

obtain clock #7) of edges from a data edge (see Fig. 5). It would have been obvious to one of ordinary skill in the art at the time of invention to use the optimum clock selected from a plurality of clocks (i.e. the clock which samples the data in the middle) as the sampling clock, in order to sample the data correctly and therefore more accurately recognize the incoming data (see column 1, lines 62 to column 2, line 9).

5. Claims 3, 4, 6, 7, 9-13, 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota and Tanabe, further in view of Bazes (US 4,975,702).

As to claim 3, Hirota and Tanabe are silent in disclosing that there is a set-up time and a holding time associated with first to N-th holding circuits. Bazes discloses that there is a specified setup time, t_s and hold time t_h , for any clocked device (see column 5, lines 18-35). Bazes discloses that the setup time requirement of the flip-flop is met if the signal has stable for at least the setup time before the next transition of the SDL tap, and similarly, the hold time requirement of the flip-flop is met if the signal has been stable for at least the hold time after the transition of the SDL tap (see column 5, lines 18-35). Bazes further discloses that the interval between each SDL output transition is given by T_r/N , where T_r is the reference clock period and N is the number of SDL taps (interpreted as the number of clock signals) (see column 4, last paragraph and column 6, first paragraph). Therefore inherently T_r/N must be equal or greater than $(t_s + t_h)$, therefore $N \leq [T_r/(T_s+T_h)]$. It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as

Art Unit: 2611

suggested by Bazes to accurately determine the location of the transitions in the digitized waveform (see column 6, first paragraph).

As to claim 4, bazes discloses that the number of clocks N is such that $N = \lceil T / (T_s + T_h) \rceil$ (see rejection of claim 3).

As to claim 6, Hirota, Tanabe, and Bazes disclose all the subject matters claimed in claim 4, except that the number of clocks N of the first to N-th clocks is such that $N=5$. However, since applicant does not disclose any advantage for using 5 clocks in the system therefore, it is a matter of design choice to sample the signal with 5 clocks and it would have been obvious to one of ordinary skill in the art at the time of invention to use 5 clocks in the system to sample the signal to meet the system requirements.

As to claim 7, Hirota, Tanabe, and Bazes disclose all the subject matters claimed in claim 1, except that the number of clocks N of the first to N-th clocks is such that $N=5$. However, since applicant does not disclose any advantage for using 5 clocks in the system therefore, it is a matter of design choice to sample the signal with 5 clocks and it would have been obvious to one of ordinary skill in the art at the time of invention to use 5 clocks in the system to sample the signal to meet the system requirements.

As to claim 9, Hirota, Tanabe, and Bazes are silent in disclosing that the number M is set to a number that ensures a set-up time and a hold time of a circuit which holds data based on the generated sampling clock. However, it would have been obvious to select the optimal clock in a place that ensures a set-up time and a hold time of a circuit, which holds data based on the

Art Unit: 2611

generated sampling clock to accurately determine the location of the transitions in the digitized waveform (see column 6, first paragraph).

As to claim 10, Hirota discloses an apparatus comprising: an edge detection circuit (see Fig. 4, 23-2) detecting between which two clock edges a data edge is located (see Fig. 5 and column 3, lines 9-30), the two edges being among edges of first to N-th clocks having the same frequency but mutually different phases (see the abstract and column 2, lines 21-29); and a clock selection circuit which selects one clock (i.e. clock #7) from among the first to N-th clocks (see column 3, lines 28-30), based on detection information from the edge detection circuit. Hirota discloses all the subject matters claimed in claim 10 except that the selected clocks has been used as a sampling clock. Tanabe, in the same field of endeavor, discloses a sampling pulse generator, which receives a plurality of clock signals having the same frequency and phase differences. Tanabe further discloses an additional signal (interpreted as data signal) is also inputted to the edge detector (see Fig. 1), wherein phase relationship data are constructed and assembled and an optimum one of the clock signals is selected and outputted based on the phase data as the recovered sampling signal (see the abstract and column 3, lines 30-45, and see column 1, lines 10-16). It would have been obvious to one of ordinary skill in the art at the time of invention to use the optimum clock selected from a plurality of clocks (i.e. the clock which samples the data in the middle) as the sampling clock, in order to sample the data correctly and therefore more accurately recognize the incoming data (see column 1, lines 62 to column 2, line 9). Tanabe further discloses that the edge

Art Unit: 2611

detection circuit comprises: a first holding circuit (see Fig. 3, e.g. 310) which holds data (CRS interpreted as data) by using the first clock (CK0), . . . a J-th holding circuit (see Fig. 3, e.g. 314), which holds data by using a J-th clock (CK4), . . . and an N-th holding circuit (see Fig. 3, e.g. 317) which holds data by using the N-th clock (CK7). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota as suggested by Tanabe to accurately determine the edge of the data (see column 4, lines 10-24) and find the optimum sampling clock. As to the last limitation of claim 10, Hirota and Tanabe are silent in disclosing that there is a set-up time and a holding time associated with first to N-th holding circuits. Bazes discloses that there is a specified setup time, t_s and hold time t_h , for any clocked device (see column 5, lines 18-35). Bazes discloses that the setup time requirement of the flip-flop is met if the signal has stable for at least the setup time before the next transition of the SDL tap, and similarly, the hold time requirement of the flip-flop is met if the signal has been stable for at least the hold time after the transition of the SDL tap (see column 5, lines 18-35). Bazes further discloses that the interval between each SDL output transition is given by T_r/N , where T_r is the reference clock period and N is the number of SDL taps (interpreted as the number of clock signals) (see column 4, last paragraph and column 6, first paragraph). Therefore inherently T_r/N must be equal or greater than $(t_s + t_h)$, therefore $N \leq [T_r/(T_s+T_h)]$. It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as suggested by Bazes to accurately determine the

Art Unit: 2611

location of the transitions in the digitized waveform (see column 6, first paragraph).

As to claim 11, bazes discloses that the number of clocks N is such that $N = \lceil T / (T_s + T_h) \rceil$ (see rejection of claim 10).

As to claims 12 and 13, Hirota, Tanabe, and Bazes disclose all the subject matters claimed in claim 10 and 11, except that the number of clocks N of the first to N-th clocks is such that $N=5$. However, since applicant does not disclose any advantage for using 5 clocks in the system therefore, it is a matter of design choice to sample the signal with 5 clocks and it would have been obvious to one of ordinary skill in the art at the time of invention to use 5 clocks in the system to sample the signal to meet the system requirements.

As to claim 15, Hirota, Tanabe, and Bazes are silent in disclosing that the number M is set to a number that ensures a set-up time and a hold time of a circuit which holds data based on the generated sampling clock. However, it would have been obvious to select the optimal clock in a place that ensures a set-up time and a hold time of a circuit, which holds data based on the generated sampling clock to accurately determine the location of the transitions in the digitized waveform (see column 6, first paragraph).

6. Claims 16 and 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota and Tanabe, further in view of Yamauchi et al. (hereafter, referred as Yamauchi) (US 5,517,155).

As to claims 16, 18, 19, and 21, Hirota and Tanabe disclose all the subject matters claimed in claims 1 and 14, except that sampling clock generation circuit,

Art Unit: 2611

further comprises: a PLL circuit having an oscillation circuit with a variably-controlled oscillation frequency, and phase-synchronizing a clock generated by the oscillation circuit with a base clock, wherein the first to N-th clocks is generated based on outputs of first to N-th inversion circuits of an odd number of stages included in the oscillation circuit. Yamauchi, in the same field of endeavor, discloses a PLL circuit (see Fig. 2) having an oscillation circuit (block 6) with a variably-controlled oscillation frequency, and phase-synchronizing a clock generated by the oscillation circuit with a base clock (see column 6, last paragraph and column 7, first paragraph), wherein the first to N-th clocks is generated based on outputs of first to N-th inversion circuits of an odd number of stages included in the oscillation circuit (see Fig. 7, column 22, paragraphs 2-3 and column 23, last paragraph). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as suggested by Yamauchi to accurately find the optimal clock synchronized with the clock of the transmitter suitable for sampling the incoming data signal.

As to claims 19 and 21, Yamauchi further discloses that at least one of a disposition of the first to N-th inversion circuits and interconnection of output lines of the first to N-th inversion circuits is performed in such a manner that phase differences between the first to N-th clocks are equal (see column 23, last paragraph).

7. Claims 17 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota, Tanabe, and Bazes further in view of Yamauchi et al. (hereafter, referred as Yamauchi) (US 5,517,155).

As to claim 17, Hirota, Tanabe, and Bazes disclose all the subject matters claimed in claim 10, except that sampling clock generation circuit, further comprising: a PLL circuit having an oscillation circuit with a variably-controlled oscillation frequency, and phase-synchronizing a clock generated by the oscillation circuit with a base clock, wherein the first to N-th clocks is generated based on outputs of first to N-th inversion circuits of an odd number of stages included in the oscillation circuit. Yamauchi, in the same field of endeavor, discloses a PLL circuit (see Fig. 2) having an oscillation circuit (block 6) with a variably-controlled oscillation frequency, and phase-synchronizing a clock generated by the oscillation circuit with a base clock (see column 6 last paragraph and column 7, first paragraph), wherein the first to N-th clocks is generated based on outputs of first to N-th inversion circuits of an odd number of stages included in the oscillation circuit (see Fig. 7, column 22, paragraphs 2-3 and column 23, last paragraph). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as suggested by Yamauchi to accurately find the optimal clock synchronized with the clock of the transmitter suitable for sampling the incoming data signal.

As to claims 20, Yamauchi further discloses that at least one of a disposition of the first to N-th inversion circuits and interconnection of output lines of the first to N-th inversion circuits is performed in such a manner that phase differences between the first to N-th clocks are equal (see column 23, last paragraph).

Art Unit: 2611

8. Claims 22 and 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota, Tanabe, and Yamauchi, further in view of Wendelrup (US 5,796,360).

As to claims 22 and 24, Hirota, Tanabe, and Yamauchi are silent in disclosing that the lines for the first to N-th clocks are interconnected in such a manner that the parasitic capacitances of lines of the first to N-th clocks are equal. Wendelrup, in the same field of endeavor discloses a controlled clock generator (see column 1, lines 8 and 9). Wendelrup further discloses that in a design for implementation on a CMOS integrated circuit, one must ensure that all of the output nodes of the logic circuitry 907 have equal parasitic capacitances (see column 7, last paragraph and Fig. 9). It would have been obvious to one of ordinary skill in the art at the time of invention to Modify Hirota, Tanabe, and Yamauchi as suggested by Wendelrup in order to have uniform delays introduced for each of the phase clocks (See column 7, last paragraph).

9. Claim 23 is rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota, Tanabe, Bazes, and Yamauchi, further in view of Wendelrup (US 5,796,360).

As to claim 23, Hirota, Tanabe, Bazes and Yamauchi are silent in disclosing that the lines for the first to N-th clocks are interconnected in such a manner that the parasitic capacitances of lines of the first to N-th clocks are equal. Wendelrup, in the same field of endeavor discloses a controlled clock generator (see column 1, lines 8 and 9). Wendelrup further discloses that in a design for implementation on a CMOS integrated circuit, one must ensure that

Art Unit: 2611

all of the output nodes of the logic circuitry 907 have equal parasitic capacitances (see column 7, last paragraph and Fig. 9). It would have been obvious to one of ordinary skill in the art at the time of invention to Modify Hirota, Tanabe, Bazes, and Yamauchi as suggested by Wendelrup in order to have uniform delays introduced for each of the phase clocks (See column 7, last paragraph).

10. Claims 25, 27, 31, and 33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota and Tanabe, further in view of Fujimori et al. (hereafter, referred as Fujimori) (US 6,477,181).

As to claims 25 and 27, Hirota discloses an apparatus comprising: an edge detection circuit (see Fig. 4, 23-2) detecting between which two clock edges a data edge is located (see Fig. 5 and column 3, lines 9-30), the two edges being among edges of first to N-th clocks having the same frequency but mutually different phases (see the abstract and column 2, lines 21-29); and a clock selection circuit which selects one clock (i.e. clock #7) from among the first to N-th clocks (see column 3, lines 28-30), based on detection information from the edge detection circuit. Hirota discloses all the subject matters claimed in claims 25 and 27 except that the selected clock has been used as a sampling clock. Tanabe, in the same field of endeavor, discloses a sampling pulse generator, which receives a plurality of clock signals having the same frequency and phase differences. Tanabe further discloses an additional signal (interpreted as data signal) is also inputted to the edge detector (see Fig. 1), wherein phase relationship data are constructed and assembled and an optimum one of the

Art Unit: 2611

clock signals is selected and outputted based on the phase data as the recovered sampling signal (see the abstract and column 3, lines 30-45, and see column 1, lines 10-16). It would have been obvious to one of ordinary skill in the art at the time of invention to use the optimum clock selected from a plurality of clocks (i.e. the clock which samples the data in the middle) as the sampling clock, in order to sample the data correctly and therefore more accurately recognize the incoming data (see column 1, lines 62 to column 2, line 9). As to the last limitation of claims 25 and 27, Neither Hirota nor Tanabe disclose a circuit which holds data, based on the sampling clock generated by the sampling clock generation circuit, and performs given processing for data transfer, based on the held data. Fujimori discloses a data communication apparatus (see Fig. 6) comprising a sampling clock generator 42 and a sound I/O 41 which writes the audio data into its internal output FIFO buffer and then reads out the data from the output FIFO buffer in accordance with the sampling pulses to transfer the read-out data to the DAC for digital-to-analog conversion (see column 6, last paragraph). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as suggested by Fujimori to improve the data communication system (see column 27, lines 16-25).

As to claims 31 and 33, Fujimori further shows a device, which performs storage processing (see Fig. 6, 31-33) on data transferred through the data transfer control device (see Fig. 6, 41 and 42) and the bus 44.

Art Unit: 2611

11. Claim 26 and 32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota, Tanabe, and Bazes further in view of Fujimori et al. (hereafter, referred as Fujimori) (US 6,477,181).

As to claim 26, Hirota discloses an apparatus comprising: an edge detection circuit (see Fig. 4, 23-2) detecting between which two clock edges a data edge is located (see Fig. 5 and column 3, lines 9-30), the two edges being among edges of first to N-th clocks having the same frequency but mutually different phases (see the abstract and column 2, lines 21-29); and a clock selection circuit which selects one clock (i.e. clock #7) from among the first to N-th clocks (see column 3, lines 28-30), based on detection information from the edge detection circuit. Hirota discloses all the subject matters claimed in claim 26 except that the selected clock has been used as a sampling clock. Tanabe, in the same field of endeavor, discloses a sampling pulse generator, which receives a plurality of clock signals having the same frequency and phase differences. Tanabe further discloses an additional signal (interpreted as data signal) is also inputted to the edge detector (see Fig. 1), wherein phase relationship data are constructed and assembled and an optimum one of the clock signals is selected and outputted based on the phase data as the recovered sampling signal (see the abstract and column 3, lines 30-45, and see column 1, lines 10-16). It would have been obvious to one of ordinary skill in the art at the time of invention to use the optimum clock selected from a plurality of clocks (i.e. the clock which samples the data in the middle) as the sampling clock, in order to sample the data correctly and therefore more accurately recognize the incoming data (see

Art Unit: 2611

column 1, lines 62 to column 2, line 9). Tanabe further discloses that the edge detection circuit comprises: a first holding circuit (see Fig. 3, e.g. 310) which holds data (CRS interpreted as data) by using the first clock (CK0), . . . a J-th holding circuit (see Fig. 3, e.g. 314), which holds data by using a J-th clock (CK4), . . . and an N-th holding circuit (see Fig. 3, e.g. 317) which holds data by using the N-th clock (CK7). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota as suggested by Tanabe to accurately determine the edge of the data (see column 4, lines 10-24) and find the optimum sampling clock. Hirota and Tanabe are silent in disclosing that there is a set-up time and a holding time associated with first to N-th holding circuits. Bazes discloses that there is a specified setup time, t_s and hold time t_h , for any clocked device (see column 5, lines 18-35). Bazes discloses that the setup time requirement of the flip-flop is met if the signal has stable for at least the setup time before the next transition of the SDL tap, and similarly, the hold time requirement of the flip-flop is met if the signal has been stable for at least the hold time after the transition of the SDL tap (see column 5, lines 18-35). Bazes further discloses that the interval between each SDL output transition is given by T_r/N , where T_r is the reference clock period and N is the number of SDL taps (interpreted as the number of clock signals) (see column 4, last paragraph and column 6, first paragraph). Therefore inherently T_r/N must be equal or greater than $(t_s + t_h)$, therefore $N \leq [T_r/(T_s + T_h)]$. It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota and Tanabe as suggested by Bazes to accurately determine the location of the transitions in the

Art Unit: 2611

digitized waveform (see column 6, first paragraph). As to the last limitation of claim 26, Hirota, Tanabe, and Bazes do not disclose a circuit which holds data, based on the sampling clock generated by the sampling clock generation circuit, and performs given processing for data transfer, based on the held data. Fujimori discloses a data communication apparatus (See Fig. 6) comprising a sampling clock generator 42 and a sound I/O 41 which writes the audio data into its internal output FIFO buffer and then reads out the data from the output FIFO buffer in accordance with the sampling pulses to transfer the read-out data to the DAC for digital-to-analog conversion (see column 6, last paragraph). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Hirota Tanabe, and Bazes as suggested by Fujimori to improve the data communication system (see column 27, lines 16-25).

As to claim 32, Fujimori further shows a device, which performs storage processing (see Fig. 6, 31-33) on data transferred through the data transfer control device (see Fig. 6, 41 and 42) and the bus 44.

12. Claims 28, 30, 34, and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota and Tanabe, and Fujimori further in view of applicant's admitted prior art (applicant's background of invention).

As to claims 28 and 30, Fujimori discloses that the data has been transferred by using bus 44 in the system (see Fig. 6). However, Fujimori does not disclose data transfer is in accordance with the Universal Serial Bus (USB) standard. Applicant in the background of invention discloses that the USB standard has the advantage of enabling the use of connectors of the same

Art Unit: 2611

standard to connect peripheral equipment such as a mouse, keyboard, and printer, which are connected by connectors of different standards, and of making it possible to implement plug-and-play and hot-plug features (see page 1). Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to use the USB standard for the reasons stated above.

As to claims 34 and 36, Fujimori further shows a device, which performs storage processing (see Fig. 6, 31-33) on data transferred through the data transfer control device (see Fig. 6, 41 and 42) and the bus 44.

13. Claims 29 and 35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hirota and Tanabe, Bazes and Fujimori further in view of applicant's admitted prior art (applicant's background of invention).

As to claim 29, Fujimori discloses that the data has been transferred by using bus 44 in the system (see Fig. 6). However, Fujimori does not disclose data transfer is in accordance with the Universal Serial Bus (USB) standard. Applicant in the background of invention discloses that the USB standard has the advantage of enabling the use of connectors of the same standard to connect peripheral equipment such as a mouse, keyboard, and printer, which are connected by connectors of different standards, and of making it possible to implement plug-and-play and hot-plug features (see page 1). Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to use the USB standard for the reasons stated above.

Art Unit: 2611

As to claim 35, Fujimori further shows a device, which performs storage processing (see Fig. 6, 31-33) on data transferred through the data transfer control device (see Fig. 6, 41 and 42) and the bus 44.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Leila Malek whose telephone number is 571-272-8731. The examiner can normally be reached on 9AM-5:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mohammad Ghayour can be reached on 571-272-3021. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Leila Malek
Examiner

Art Unit: 2611

Art Unit 2611

L.M


MOHAMMED GHAYOUR
SUPERVISORY PATENT EXAMINER